

ALUMINIUM ADAPTOR FILTER HEADS

CF16



The filter head Part Number CF16 is threaded M16x1.5mm to take the widest range of Spin on Fuel filters available. (Please note suggested uses below)

The inlet and outlet ports are threaded 1/2-BSP and head is fitted with a vent tap.

FILTER HEAD PART No.	SUGGESTED USE	FILTER PART No.	MICRON RATING	RECOMMENDED MAX FLOW RATE	LENGTH (INC. ADAPTER)
CF16	PRIMARY DIESEL WATER SEPERATOR	Z172	11 *	4,0 L/min	264 mm
CF16	SECONDARY DIESEL SEPERATOR	Z103 Z130 Z75 Z65 Z108	4 *	3.5 L/min 2.5 L/min 1.5 L/min 1.0 L/min 1.5 L/min	264 mm 192 mm 176 mm 139 mm 194mm

CF34



FILTER HEAD PART No.	SUGGESTED USE	FILTER PART No.	MICRON RATING	RECOMMENDED MAX FLOW RATE	LENGTH (INC. ADAPTER)
CF34	AIR BREATHER	Z25A	4 *	1250 L/min	141 mm
CF34	OIL	Z72 Z45 Z95 Z100 Z217 Z123 Z28 Z159	11 *	50 L/min 40 L/min 30 L/min 35 L/min 20 L/min 20 L/min 15 L/min 10 L/min	234 mm 222 mm 172 mm 179 mm 139 mm 146 mm 129 mm 126 mm

* Micron rating = Nominal @ 50% retention efficiency